

ONAN P4500i



Power your world

4,500-watt digital inverter
gasoline portable generator

3,700 running watts | 4,500 peak watts

FEATURES

- RV- and camper-ready with 30A TT-30R outlet
- Two 5V USB ports for charging sensitive electronics, such as phones or tablets
- Telescoping handle for easy transportation
- Dependable 224cc OHV 4-stroke Cummins Onan engine
- Limited 3-year warranty



DIGITAL INVERTER GENERATOR

Efficient, clean energy that requires little maintenance



PUSH BUTTON AND REMOTE START

Pull cord backup



QUIET AND DURABLE

Double insulated



PARALLEL CAPABLE

Parallels with another P4500i, P4500iDF, or P2500i generator



FUEL-EFFICIENT

3.4-gallon fuel tank that runs 18 hrs at 25% load



LIGHTWEIGHT

At 98 lbs, and with a telescoping handle and wheels, it's lighter and easier to manage




United States and Canada Model
Not for sale in California

ONAN P4500i

Specifications

Part number	A074Z436
Gasoline peak watts	4,500
Gasoline running watts	3,700
Peak amps at 120V	37.5 amps
Running amps at 120V	30.8 amps
AC voltage	120 volts
DC voltage	5 volts
AC frequency	60 Hz
Parallel capable	Yes
Total harmonic distortion (THD)	≤3%
Starting system	Electric, remote, recoil
Battery included	Yes
Battery charger included	Yes
Remote start fob included	Yes (paired at factory)
Remote start distance (feet/meters)	99 ft (30 m)
Engine displacement	224cc
Engine brand	Cummins Onan
Engine type	OHV 4-stroke
Engine speed	Variable
Operational volume	As low as 52 dBA
Carburetor kit required to operate at altitude	Yes, above 2,000 ft
Economy mode switch	Yes
Built-in inverter	Yes
Engine lubrication	Splash
Recommended oil	SAE 10W-30
Oil bottle size (included)	.63 qt / 20.3 oz
Oil capacity (quarts/ounces)	.63 qt / 20.3 oz
Low oil shutdown	Automatic
Fuel type	Unleaded gasoline, 10% ethanol or less
Fuel shut off	Manual
Fuel tank material	Steel
Fuel tank capacity (gallons/liters)	3.4 gal (12.8 L)
Run time at %25 load (hrs)	15.6 hrs
Run time at %50 load (hrs)	10 hrs
Gasoline fuel gauge	Yes
Choke type	Automatic
AC outlets	(1) 120V 30A (TT-30R) (1) Duplex 120V 20A (5-20R)
DC outlets	(2) 5V USB ports
Ground	Floating neutral
Covered outlets	Yes

Manual transfer switch ready	No
GFCI outlets	No
LED data center	Yes
RV-ready outlet	Yes
Overload protection (circuit breaker)	Yes
Handle style	Telescoping handle
Emissions	EPA
Canada CSA compliant	Yes
Wheel kit included	Yes (assembled)
Wheel size	5.5 in diameter, 1.5 in thick
Spark arrestor	Yes
Residential warranty	3-year limited
Commercial warranty	1-year comprehensive
Assembled length in (mm)	24.5 in (622 mm)
Assembled width in (mm)	18.3 in (463 mm)
Assembled height in (mm)	20.5 in (520 mm)
Carton length in (mm)	29.3 in (744 mm)
Carton width in (mm)	21.3 in (541 mm)
Carton height in (mm)	24.0 in (610 mm)
Dry unit weight lb (kg)	98.0 lb (44 kg)
Shipping weight lb (kg)	119.1 lb (54 kg)



DISPLAY INFORMATION

F9.31	P1.21	2.8L	U122	22:31
Remaining run time	Power output (kW)	Fuel level (Liters)	Voltage	Lifetime run hours



Cummins Inc.
Box 3005
Columbus, IN 47202-3005
U.S.A.

cummins.com

Bulletin 6543401 Produced in U.S.A. Rev. 3/25
©2025 Cummins Inc.